HOMEBOND™
HOLD BEYOND LIMITS

CATALOGUE 2026



PRODUCT CATALOGUE

Tile & Stone Adhesives

Tiles & Stone Adhesives / Waterproofing / Repairs / Maintenance / Stonecare

ABOUT US

Company Story

HOMEBOND is a global brand that manufactures tiles & stone Adhesives, waterproofing, repairs, maintenance & stonecare Products which are formulated with world-class german Polymers & technology. It has developed a comprehensive Product range based on international standards to facilitate Global construction chemical and building materials market. The brains behind the product development have a combined Experience of more than 120 years in the same industry. With This abundance of experience, the company is ready to Build better!

120+
YEARS COMBINED EXPERIENCE

German
POLYMERS & TECHNOLOGY

Global
INTERNATIONAL STANDARDS

IS 15477
CM/L-7900128218

HOMEBOND™
HOLD BEYOND LIMITS

POLYMER MODIFIED TILES ADHESIVE

HX-03

TYPE-I



MATERIAL TO BE FIXED

All Type Of Ceramic & Vitrified Tiles On Wall And Tile On Tile On Floor, Also Suitable For Terra Cotta, Pavers, Brick, Precast Terrazzo, Etc...

ON SURFACE / SUBSTRATE

Cement-Based Screeds & Mortars, Cement-Based Plasters/Renders, Concrete Surfaces, Bricks, AAC Blocks, Existing Tiles & Stones, Other Cement-Based Surfaces.

AREA OF APPLICATION

Flooring And Walls, For Internal Application & External Shaded Area, External Area*, Dry & Wet Area, New Construction & Renovation, Domestic Applications, Commercial Applications.

*Standard Tiles Up To 9MM Recommended For Any Big Format Tile & Stone Fitting Application Consult HOMEBOND Technical Team.

PACK

20 KG

For Internal Floor & Wall | Tile On Tile Application | Non-Slip Adhesive | For Tile & Natural Stone | Polymer Modified | Low VOC

HOMEBOND™
HOLD BEYOND LIMITS



TECHNICAL DATA SHEET

HX-03 TYPE-I

TYPE-I Tile Adhesive (grey) High Polymer Modified, Cement Based Tile Adhesive, Suitable To Install All Types Of Ceramic & Vitrified Tiles On Floor And Small To Medium Format Of Tiles On Wall.

APPLICATION PROPERTIES

TEST	RESULT
Powder : Water Mixing Ratio	1 : 0.25 By Weight
Chemical Curing Time	3-4 Minutes
Pot Life (In Shade)	120 Minutes Approx
Open Time	20 Minutes Approx
Adjusting Time	20 Minutes Approx
Waiting Time Before Grouting	24 Hours

Remark: These Test Results Are From Laboratory Test. They Could Be Slightly Different From On-Site Results Because Of The Differences In Applications And Conditions.

CERTIFIED STANDARD

TESTING PROPERTY	REQUIREMENT	TEST RESULTS
Tensile Adhesion At Dry Condition	≥ 0.5 N/mm²	0.5-0.8 N/mm²
Tensile Adhesion At Wet Condition	-	0.5-0.8 N/mm²
Shear Adhesion At Dry Condition	≥ 1.0 N/mm²	1.1-1.5 N/mm²
Shear Adhesion At Wet Condition	-	1-1.4 N/mm²
Shear Adhesion At Heat Ageing	-	1-1.4 N/mm²
Slip Resistance (T)	-	0.3-0.5 mm

COVERAGE

Approx. 5-6M²/20 Kg. Bag At 3MM Thickness (Using 6MM x 6MM Notch) Approx. 1.2 Kg./M² Per MM Of Thickness.

SHELF LIFE

12 Months For Sealed Pack When Stored Under Cover, Out Of Direct Sunlight, Damp Proof Condition And Protect From Extremes Of Temperature.

HOMEBOND™
HOLD BEYOND LIMITS

POLYMER MODIFIED TILES ADHESIVE

HX-06

TYPE-II



MATERIAL TO BE FIXED

All Type Of Ceramic Tiles, Terra Cotta, Brick, Vitrified Tiles Etc...

ON SURFACE / SUBSTRATE

Cement-Based Screeds, Cement-Based Plasters, Other Cement Based Surfaces.

AREA OF APPLICATION

New Construction Flooring And Walls, For Internal Application

*Only Recommended To Fix On Internal Floor, Consult With HOMEBOND Technical Team For Fixing On EXTERNAL Wall Application.

PACK

20 KG

For Internal Floor & Wall
Tile On Tile Application
Non-Slip Adhesive
For Tile & Natural Stone
Polymer Modified
Low VOC

HOMEBOND™
HOLD BEYOND LIMITS



TECHNICAL DATA SHEET

HX-06 TYPE-II

TYPE-II Tiles Adhesive Is High Polymer Modified, Cement-Based Tile Adhesive, Suitable To Install Small To Medium Format Of Ceramic Tiles, Vitrified Tiles & Porcelain Tiles On Floor And Wall. HX-06 Tile Adhesive Can Also Be Used For The Fixing Of Ceramic Tile On Tile Applications On Floor.

APPLICATION PROPERTIES

TEST	RESULT
Powder : Water Mixing Ratio	1 : 0.26 By Weight
Chemical Curing Time	3-4 Minutes
Pot Life (In Shade)	120 Minutes Approx
Open Time	20 Minutes Approx
Adjusting Time	25 Minutes Approx
Waiting Time Before Grouting	24 Hours

Remark: These Test Results Are From Laboratory Test. They Could Be Slightly Different From On-Site Results Because Of The Differences In Applications And Conditions.

CERTIFIED STANDARD

TESTING PROPERTY	REQUIREMENT	TEST RESULTS
Tensile Adhesion At Dry Condition	≥ 1.0 N/mm²	1.2-1.6 N/mm²
Tensile Adhesion At Wet Condition	≥ 1.0 N/mm²	1.0-1.4 N/mm²
Shear Adhesion At Dry Condition	≥ 1.25 N/mm²	1.3-1.7 N/mm²
Shear Adhesion At Wet Condition	-	1.0-1.4 N/mm²
Shear Adhesion At Heat Ageing	-	1.0-1.4 N/mm²
Slip Resistance (T)	≤ 0.5 mm	0.3-0.5 mm

COVERAGE

Approx. 5-6M²/20 Kg. Bag At 3MM Thickness (Using 6MM x 6MM Notch) Approx. 1.2 Kg./M² Per MM Of Thickness.

SHELF LIFE

12 Months For Sealed Pack When Stored Under Cover, Out Of Direct Sunlight, Damp Proof Condition And Protect From Extremes Of Temperature.



POLYMER MODIFIED TILES ADHESIVE

HX-09

TYPE-III

MATERIAL TO BE FIXED

All Type Of Ceramic Tiles, Terracotta, Pavers, Brick, Vitrified Tiles, Large Format Tiles, Precast Terrazzo, Natural Stones, Mosaic Tiles, Glass Mosaic.

ON SURFACE / SUBSTRATE

Cement-Based Screeds & Mortars, Cement-Based Plasters/Renders, Concrete Surfaces, Bricks, AAC Blocks, Existing Tiles & Stones, Other Cement-Based Surfaces.

AREA OF APPLICATION

Flooring And Walls, For Internal Area & External Area, Dry, Wet & Moist Area, Like Saunas, Spa And Fountains. New Construction & Renovation, Domestic Application, Commercial Applications.

*Only Recommended For Small To Medium Size Marble, Granite And Artificial Marble. For Big Size Marble Application Consult With The HOMEBOND Technical Team.

PACK

20 KG

For Internal Floor & Wall | Tile On Tile Application | Non-Slip Adhesive | For Tile & Natural Stone | Polymer Modified | Low VOC

HOMEBOND™
HOLD BEYOND LIMITS



TECHNICAL DATA SHEET

HX-09 TYPE-III

TYPE-III Tile Adhesive Is A Premium, Water & Frost Resistant, Highly Polymer Modified Cementitious Wall And Floor Tile Adhesive Especially Formulated For Fixing Mosaic Tiles, Ceramic And Glass Mosaic. It Is Also Suitable For Fixing Ceramic, Vitrified Wall And Floor Tiles, Metal Or Glass Tiles, Marble, Granite, Quartz Stone, Terrazzo And Other Natural Stone In Interior And Exterior Locations.

APPLICATION PROPERTIES

TEST	RESULT
Powder : Water Mixing Ratio	1 : 0.27 By Weight
Chemical Curing Time	3-4 Minutes
Pot Life (In Shade)	120 Minutes Approx
Open Time	25 Minutes Approx
Adjusting Time	30 Minutes Approx
Waiting Time Before Grouting	24 Hours

Remark: These Test Results Are From Laboratory Test. They Could Be Slightly Different From On-Site Results Because Of The Differences In Applications And Conditions.

CERTIFIED STANDARD

TESTING PROPERTY	REQUIREMENT	TEST RESULTS
Tensile Adhesion At Dry Condition	≥ 1.5 N/mm²	1.5-2 N/mm²
Tensile Adhesion At Wet Condition	≥ 1.0 N/mm²	1.0-1.5 N/mm²
Shear Adhesion At Dry Condition	≥ 1.5 N/mm²	1.5-2 N/mm²
Shear Adhesion At Wet Condition	≥ 1.0 N/mm²	1.0-1.5 N/mm²
Shear Adhesion At Heat Ageing	≥ 1.0 N/mm²	1.0-1.4 N/mm²
Slip Resistance (T)	≤ 0.5 mm	0.3-0.5 mm

COVERAGE

Approx. 5-6M²/20 Kg. Bag At 3MM Thickness (Using 6MM x 6MM Notch) Approx. 1.2 Kg./M² Per MM Of Thickness.

SHELF LIFE

12 Months For Sealed Pack When Stored Under Cover, Out Of Direct Sunlight, Damp Proof Condition And Protect From Extremes Of Temperature.

HOMEBOND™
HOLD BEYOND LIMITS



3-PART EPOXY TILE JOINT FILLER

Epoxy Grout

FOR FLOOR & WALL

DESCRIPTION

HOMEBOND Epoxy Grout is a premium, high-performance 3-part epoxy grout engineered for durability and long-lasting performance. Suited to a wide range of applications, it brings together strength, aesthetic appeal and easy maintenance — the preferred choice for residential and commercial installations alike.

DESIGN FREEDOM

Available in 23 shades, HOMEBOND Epoxy Grout lets you create a classic or a contemporary look, with joints that deliver not only beauty but also durability and ease of care.

AREA OF APPLICATION

Residential kitchens & bathrooms · Commercial spaces · Pools & spas · Outdoor environments · High-traffic areas

KEY FEATURES

- For internal floor & wall, swimming pool
- Polymer modified
- High strength
- Crack free
- Waterproof
- Stain-free & chemical resistant
- Easy to clean
- Low VOC
- Available in multiple colours

PACK

1 KG · 5 KG

HOMEBOND™
HOLD BEYOND LIMITS



TECHNICAL DATA SHEET

Epoxy Grout 3-PART

APPLICATION PROPERTIES

PARAMETER	RESULT
Joint Width	15 mm
Pot Life	50 min
Time to Foot Traffic	24 hrs
Time to Heavy Traffic	48 hrs
Specific Gravity	1.6 to 1.7 kg/ltr
Shrinkage	No Shrinkage
Water Cleaning	< 60 min
Setting Time	3 hrs
Sag	No Sagging
Compressive Strength	> 6500 PSI
Tensile Strength	> 1300 PSI

APPLICATION METHOD

01 Clean the joints and tile surface with a brush and scrub pad.

02 Mix Part A and Part B thoroughly in a bucket, then slowly add Part C (filler powder) to form a homogeneous mix.

03 Apply the mix into the joints with an applicator blade.

04 Allow 60–90 minutes for the joints to set.

05 Clean up any spillage with shampoo water and a sponge.

06 Leave the area undisturbed to dry for 24 hours.

07 The surface is now glossy, ultra-durable and ready to use.

SAFETY

Always wear hand gloves while using HOMEBOND Epoxy Grout.

SHELF LIFE

3 years from the date of manufacture in unopened condition. Store in a cool and dry place.

HOMEBOND™
HOLD BEYOND LIMITS



SHADE CARD

Epoxy Shades 23 SHADES

001 Bright White	002 Amezon Red
026 Smoke Grey	028 Teracotta
035 Platinum	004 Dasty Rose
029 Dark Grey	30 Jesalmer
007 Midnight Black	036 Grain
041 Iron Grey	045 Laana
009 Burgundy	042 Ivory
046 Coffee Brown	019 Ivy
017 Mocha	022 Pinch Green
008 Choco	024 Sky Blue
039 Wine Red	025 Sapphire
016 Canyon Red	

Shades shown are indicative; actual colour may vary slightly.

HOMEBOND™
HOLD BEYOND LIMITS



FORMAT

Pouch

POLYMER MODIFIED CEMENT GROUT

Tile Grout

UNSANDED · CEMENT BASED

DESCRIPTION

HOMEBOND Tile Grout is a polymer-modified, multi-colour cement grout — the right bonding material for filling joints in all types of wall and floor tiles. Resistant to shrinkage and cracking, it fills wall and floor tile joints from 1 mm to 5 mm wide, for both interior and exterior applications. Made with colour-fast pigments and fine graded aggregates to match your tiles.

ADVANTAGES

Wide joint bridging (up to 5 mm) · Exceptional colour stability · Excellent workability: smooth, easy to spread and easy to clean up · Non-shrink, will not crack · Flexible enough to withstand pressure from the expansion and contraction of tiles

KEY FEATURES

- Polymer modified
- High strength
- Multiple colours
- Unsanded cement based tile joint filler
- Polymerised tile joint filler
- Ready to use
- Provides waterproofing
- Prevents cracking in tile joints
- Stain & acid resistant
- Easy to clean
- Durable
- Water resistant tile joints



TECHNICAL DATA & SHADES

Tile Grout

APPLICATION PROPERTIES

PARAMETER	RESULT
Compressive Strength	
After 07 days	10.30 MPa
After 28 days	16.80 MPa
Flexural Strength	2.56 MPa
Tensile Strength	2.56 MPa
Pot Life	2–3 hrs

APPLICATION METHOD

01	Clean the application area.
02	Pour 300 to 350 ml of water into a bucket.
03	Add 1 kg of HOMEBOND Tile Grout.
04	Mix thoroughly, preferably with a mechanical stirrer, or by hand.
05	Let the mix stand for 5 minutes.
06	Apply the grout on the prepared surface with a float.
07	Check that the joints have hardened.
08	Remove excess paste from the tile surface with a damp cloth.
09	Wait 24 hours — the surface is then ready for use.

GROUT COLOURS

- White (Running)
- Ivory (Running)
- Jesalmer
- Terracotta
- C. Brown
- A. Blue
- Sor. Blue
- Grey
- Black

SHELF LIFE

12 months from the date of manufacture in unopened condition. Store in a cool and dry place.

Shades shown are indicative; actual colour may vary slightly.

HOMEBOND™
HOLD BEYOND LIMITS



NET VOLUME

1 L

PROFESSIONAL TILE CARE

Tile Cleaner

DAILY USE FORMULA

DESCRIPTION

HOMEBOND Tile Cleaner is a powerful, fast-acting formula that removes tough dirt, grease, grime, soap scum and other stains from all types of tiles, leaving them clean, shiny and fresh. Designed for regular cleaning and daily maintenance, it is ideal for both interior and exterior use.

SUITABLE FOR

Ceramic & vitrified tiles · Porcelain tiles · Glazed & unglazed ceramic tiles · Glass tiles · Natural stone

ADVANTAGES

Powerful formula · Fast acting · Easy to apply · Removes cement film

KEY FEATURES

- Removes tough stains
- Deep cleaning action
- Safe on tiles
- Shine finish
- For internal & external floor & wall
- Dilute with water
- Easy to use
- Protects the colour & shine of tiles
- Removes difficult stains
- Powerful cleaning for all types of tiles

HOMEBOND™
HOLD BEYOND LIMITS



DIRECTIONS & USAGE

Tile Cleaner

DIRECTIONS FOR REGULAR USE

01	Dilute 50 ml in 5 litres of water.
02	Apply on the surface and scrub gently.
03	Rinse with clean water and dry.

FOR DIFFICULT STAINS

01	Shake the bottle very gently and pour the cleaner onto the stained surface.
02	Leave it for 2–3 minutes to react with the stain.
03	Rub the surface with a scrub pad, adding a little more cleaner if it feels dry.
04	Rinse with water and repeat if necessary.

SURFACES TO BE CLEANED

Stain cleaning for ceramic tiles, glazed tiles, porcelain tiles, vitrified tiles, glass mosaic tiles and sanitaryware. Removes moss and wax from concrete, asbestos, terrazzo and ceramics. Cleans surfaces before and after the application of epoxy products, and natural stones.

AREA OF APPLICATION

Floor and wall tiling in kitchens, bathrooms, toilets, garages, factories, general building sites and residential tiling. Internal and external, domestic and commercial tiling areas. Routine tile cleaning with a mop in bathrooms and other tiled areas.

PRECAUTIONS

Keep out of reach of children. Avoid contact with eyes; in case of contact, rinse thoroughly with water. Do not swallow; if swallowed, seek medical advice immediately. This is an acid-based cleaner — handle with care and avoid contact with metals. Always protect neighbouring surfaces such as wood, carpet, metal and landscaping; repeated acid washing may damage some surfaces.

SHELF LIFE

1 year from the date of manufacture in unopened condition. Store in a cool and dry place.

HOMEBOND™

HOLD BEYOND LIMITS

HEAD OFFICE

HOMEBOND

612, Latest Business Center, At. Mahendranagar Chowkdi,
Morbi - 363642 (Gujarat) INDIA.

GET IN TOUCH

info@homebond.in

www.homebond.in

Customer Care **+91 97371 04915**